

Clicker Press

Swing arm clicker presses are used for a wide variety of die cutting applications. The most common uses are cutting soft to semi-rigid materials such as fabrics, leather, cork, rubber, foam and other like materials. Our clicker presses are used in many laboratories and testing facilities.

Features

- Completely hydraulic and made of strong casting material, ensuring powerful, yet quiet running.
- Ensures maximum beam strength and performance. All moving parts are made of hardened steel and are self-lubricating
- Automatic stroke end setting
- Different height cutting die without adjustment
- Control push buttons with built in device for 3/10 of second maximum delay operation to ensure safety
- Overload protection
- 1 year warranty on parts, excluding cutting pads

Clicker Press, Hydraulic Model SE8

KFG-2010

Cutting table 12 x 24 inches

Top arm width 12 inches

Cutting pressure 8 tons

Maximum stroke 3.5 inches

Dimensions /weight 24 x 27 x 53 inches x 946 lbs

Clicker Press, Hydraulic Model SE20C

KFG-2010B

Cutting table 14.5 x 36 inches

Top arm width 14.5 inches

Cutting pressure 20 tons

Maximum stroke 3.5 inches

Dimensions /weight 36 x 33 x 56 inches x 1350 lbs

KFG-2010A

Replacement cutting bed for KFG-2010

KFG-2010C

Replacement cutter bed for KFG-2010B

