



Machine	Washer KFG-2314	Dryer KFG-2314A
Version	Electric	Heat Pump or Vented
Application Area	Residential and Industrial	Residential and Industrial
Load Capacity	18 lb.	18 lb.
Machine Exterior	Stainless Steel or Lotus White	Stainless Steel or Lotus White
Machine Dimensions	33.5"H x 23.8" W x 28.25" D	33.5"H x 23.8" W x 30.6"D (HP) 33.5"H x 23.8" W x 28.25" D (Vented)
Drum Volume	19 gallon / 73 liter	34 gallon / 130 liter
Spin Speed	1500 rpm	-
G Force	704	-
Languages	32	32
Weight	227 lb.	114 lb.
Electrical Connection (Standard)	2 AC (2-pole) 208V-240V 60Hz	2 AC (2-pole) 208V-240V 60Hz
Fuse Rating (Standard)	2-pole 30 A	2-pole 30 A
Plug Type	NEMA L6-30	NEMA L6-30
Total Rated Load	4.0-5.2 kW	1.2 kW (HP), 3.2 - 4.2 kW (Vented)
Cold Water Connection	1 x cold water ½" hose with ¾" threaded union	-
Hot Water Connection	1 x hot water ½" hose with ¾" threaded union	-
Drainage Options / Exhaust Options	Sink, floor drain, or stand pipe	Drainage: sink, floor drain, or stand pipe (HP) Exhaust: 4" (100mm) hard or flexible pipe (Vented)
Vent Diameter	-	Ventless (HP), Vented (Vented)