

THE ECONOMIC 3D MEASURING SOLUTION



MEASURING ARM BACES 6 AXES

The Baces measuring arm has an internal calibration ensured by an aluminium and carbon fiber mechanical structure, **making it extremely lightweight and stable**.

▶ PRODUCT ADVANTAGE

Baces arm is an entry level solution used for most of measuring application. It has a good quality for its value.

Its lightness allows to probe longer and without effort.

Temperature compensation

The Baces arm is a portable solution which is used either in metrological department or in the workshop. The temperature probes fit the measurements in reference to temperature variations.

Compatible software: Metrolog, Polyworks, Geomagic, Powerinspect, Capps, etc.



TECHNICAL SPECIFICATIONS

| | | | Probing performances* | |
|-----------------------|-----------|----------------|----------------------------|---------------------|
| | Arm model | Working volume | Single point repeatability | Volumetric accuracy |
| SERIE 100 CARBON | M | 2.6 m | 0.028 mm | 0.044 mm |
| | G | 3.2 m | 0.045 mm | 0.064 mm |
| | XG | 4.2 m | 0.072 mm | 0.097 mm |
| | XL | 4.6 m | 0.094 mm | 0.120 mm |
| SERIE 200 ALUMINUM | М | 2.6 m | 0.040 mm | 0.065mm |
| | G | 3.2 m | 0.068 mm | 0.095 mm |
| | XG | 4.2 m | 0.098 mm | 0.210 mm |
| | XL | 4.6 m | 0.120 mm | 0.350 mm |

All specifications are subject to change without notification

The Baces arm is available in series 100 (more accurate, with carbon fiber tubes) and series 200 (more competitive, with aluminium tubes).

HARDWARE SPECIFICATIONS

Operating temperature range: 10-45 °C

Power supply: universal worldwide voltage 100-250V

Humidity: 95%, non condensing - IP51



^{*} According to ASME B89 4.22