

Product information

Mobile roughness measuring instrument MarSurf PS 10

Product features

"SMAHRT Surf" – simple, smart and mobile

- Compact roughness measuring instrument for mobile use
- Simple and intuitive to use: as easy as using a smart phone
- Large, illuminated 4.3" TFT touch display
- Adjustable display
- Data backup as TXT, X3P, CSV or PDF file
- Create complete PDF measuring records directly in the measuring instrument
- Customized comments for the PDF measuring record can be entered directly into the MarSurf PS 10
- Mains-independent operation: Over 1200 measurements without having to recharge the instrument
- An all-in-one solution. Small and lightweight (approx. 500 g)
- Instrument flexibility: removable drive unit
- 31 surface parameters: offer the same range of functions as a laboratory instrument
- Roughness standard stored within housing aids in reducing errors
- Quick access to your frequently used functions via the Favorites list in the display
- Automatic cutoff selection, so even non-specialists can be sure of getting the correct measuring results
- Additional version with transverse drive unit available as MarSurf PS 10 C2 (item number 6910235)

Application

- For shafts and housing components
- For large machines
- For large workpieces
- For milled and turned parts
- For ground and honed workpieces
- On the production line or directly on the machine; ideal for rapid testing of the surface roughness of a workpiece

Introduction

sMAHRtSurf - Simple, smart and mobile



Item no.: 6910230

Technical data

Positioning speed	0.5; 1.0
Measuring principle	Stylus method
Measuring units	metric/inches
Measuring force (N)	0,00075
Filter according to ISO/JIS	Gaussian filter as per ISO 16610-21 (formerly ISO 11562), special filter as per DIN EN ISO 13565-1, Lambda s filter as per DIN EN ISO 3274 (can be switched off)
Cutoff lc according to ISO/JIS	0,25 mm, 0,8 mm, 2,5 mm, automatic filter detection
Short stroke under ISO/JIS	Selectable
Number n of sampling length according to ISO/JIS	Selectable: 1 to 16
Data interface	USB, MarConnect (RS-232), Micro SD slot for SD / SDHC cards up to 32 GB
Languages	German, English, French, Italian, Spanish, Portugese, Dutch, Swedish, Russian, Polish, Czech, Japanese, Chinese, Korean, Hungarian, Turkish, Romanian
Storage capacity	Min. 3900 profiles, min. 500,000 results, min. 1500 PDF records, expandable to 32 GB with Micro SD card
Probe	Inductive skidded probe
Calibration function	Dynamic; Ra, Rz, Rsm
IP protection category	IP 40
Weight (gross)	1.92 KG
Dimensions in mm	160 mm x 77 mm x 50 mm
Other	Lock/password protected, date/time
Traversing length according ISO 12085 (MOTIF)	1 mm, 2 mm, 4 mm, 8 mm, 12 mm, 16 mm
Evaluation lenth ln according to ISO/JIS	1.25 mm, 4.0 mm, 12.5 mm
Stylus	2 µm
Parameters	Ra, Rq, Rz (Ry (JIS) is equivalent to Rz), Rz (JIS), Rmax, Rp, RpA (ASME), Rpm (ASME), Rpk, Rk, Rvk, Mr1, Mr2, A1, A2, Vo, Rt, RPc, Rmr (tp (JIS, ASME) is equivalent to Rmr), RSm, RSk, RS, CR, CF, CL, R, Ar, Rx, R3z
System of protection	IP 40
Rechargeable batteries	Lithium-ion battery, min. 1200 measurements
Wide range power supply	100 to 264 V
Measuring range mm	0.350
Profile resolution	8 nm
Traversing length Lt according ISO/JIS	1.5 mm, 4.8 mm, 15 mm, N x Lc, variable, automatic

Product information

Mobile roughness measuring instrument MarSurf PS 10

Dimensions

Dimensions in mm	160 mm x 77 mm x 50 mm
------------------	---------------------------

Product information

Mobile roughness measuring instrument MarSurf PS 10

Accessories

Order no.	Designation	Product type
6850540	PHT pick-up extension 80 mm	PHT (80 mm)
6111520	Standard probe 2 µm	PHT 6-350
6111526	Standard probe 5 µm	PHT 6-350/5µm
6111527	Standard probe 10 µm	PHT 6-350/10µm
6111521	Probe for bores with a dia. larger than 3 mm	PHT 3-350
6111524	Probe for grooves	PHT 11-100
6111525	Probe for concave and convex surfaces	PHTR-100
6111522	Probe for gear tooth flanks	PHTF 0.5-100
6111523	Probe for metal sheets	PT 150
6710803	Measuring stand 300 mm with cast iron base	ST-D
6710806	Measuring stand 300 mm with granite plate	ST-F
6710807	Measuring stand 300 mm with granite plate and T-slot	ST-G
2247086	Adjustable mounting bracket to connect to 814 SR	814 Sh
4426100	Digital height gage	814 SR
4426101	Digital height gage	814 SR
4102357	Data connection cable USB	16 EXu
4102603	Data cable USB bidirectional	DK-U1
6710401	V-block	PP
6710604	Parallel vice	PPS
6710529	XY table	CT 120
4246819	Set of miniature precision vises	109 PS
6820420	Roughness standard with Mahr calibration certificate, profile depth	PRN 10